

ADVA® Flow 375 (BV/FM)

Plasticizer for concrete acc. to EN 934-2:T2. Superplasticizer for concrete acc. to EN 934-2:T3.1/3.2.

Product Description

ADVA®Flow 375 (BV/FM) is used as a superplasticizer for the production of high-quality precast elements in fair-faced concrete quality. The product allows to realize concrete with high capable of flow and strong cohesion. After a few hours, the concrete will show excellent strength developments.

Compatibility

With Cements:

ADVA®Flow 375 (BV/FM) can be used with most types of normal cements. For use with special cements we recommend you to contact GCP Construction Products.

With Other Admixtures:

ADVA [®]Flow 375 (BV/FM) should not be premixed under any circumstances with other admixtures. The performance of the product will be affected by the presence of other chemicals and we recommend that GCP be consulted in such circumstances.

We recommend that all admixtures be added separately into the mix.

Method Of Use

ADVA®Flow 375 (BV/FM) is supplied ready for use. When adding ADVA®Flow 375 (BV/FM) in the factory, we recommend the dosage together with the gauging water or much better as the latest component. The mixing time after dosage of the agent depends on the mixing energy, whereas a minimum mixing time of 60 seconds must be followed.

Addition of any other chemical admixture should be undertaken separately.

Addition Rates

Recommended Dosage:

200mL - 4280 mL per 100 kg cement 0.2%-4.28% (v/w) by wt. of cement

As with most products of this type, the magnitude of the effect obtained with ADVA®Flow 375 (BV/FM) is governed by the quantity of product used, w/c ratio, and the specific nature of the concrete and constituent materials.



It is necessary therefore to assess performance under site conditions using actual materials to determine optimum performance and dosage. For advice and assistance with trials, please consult your local GCP representative.

Technical Data

PRODUCT	ADVA® FLOW 375 (BV/FM)
Color	Brown
Physical form	Liquid
Density (g/cm3)	1.06 (+/-) 0.02
pH-Value	5.5 (+/-) 1.0
Chloride content (m%)	< 0.1
Alkali content (m%)	< 1.0

Packaging

ADVA®Flow 375 (BV/FM) is supplied in 205L non-returnable drums. Alternatively, 1,000L totes and bulk deliveries can be arranged.

Storage

ADVA®Flow 375 (BV/FM) should be stored under shelter and away from extreme cold or heat at all times.

Shelf life in manufacturer's drum is 12 months from date of manufacture. Shelf life in bulk storage is 12 months from date of delivery.

Safety and Handling

Read and understand the product label and Safety Data Sheet (SDS). All users should acquaint themselves with this information prior to working with the products and follow the precautionary statements. SDSs can be obtained by contacting your local GCP representative or office.

gcpat.sg | For technical information: asia.enq@gcpat.com

We hope the information here will Abe helpful. It is based on data and knowledge considered to be true and accurate, and is offered for consideration, investigation and verification by the user, but we do not warrant the results to be obtained. Please read all statements, recommendations, and suggestions in conjunction with our conditions of sale, which apply to all goods supplied by us. No statement, recommendation, or suggestion is intended for any use that would infringe any patent, copyright, or other third party right.

ADVA is a trademark, which may be registered in the United States and/or other countries, of GCP Applied Technologies, Inc. This trademark list has been compiled using available published information as of the publication date and may not accurately reflect current trademark ownership or status.

© Copyright 2018 GCP Applied Technologies, Inc. All rights reserved.

GCP Applied Technologies Inc., 2325 Lakeview Parkway, Alpharetta, GA 30009, USA

GCP (Singapore) Pte. Ltd, 25 Tanjong Penjuru, Singapore 609024.

This document is only current as of the last updated date stated below and is valid only for use in Singapore. It is important that you always refer to the currently available information at the URL below to provide the most current product information at the time of use. Additional literature such as Contractor Manuals, Technical Bulletins, Detail Drawings and detailing recommendations and other relevant documents are also available on www.gcpat.sg. Information found on other websites must not be relied upon, as they may not be up-to-date or applicable to the conditions in your location and we do not accept any responsibility for their content. If there are any conflicts or if you need more information, please contact GCP Customer Service.

Last Updated: 2025-05-15